KANTÁKING

High Range Wireless Display

Seven segment LED wireless displays with inbuilt wireless provision are designed for simplicity of installation. These displays can be interfaced in three ways:

- With indicators having inbuilt wireless provision
- Using wireless transmitter to be connected on TTD port
- Using wireless transmitter to be connected on RS232 port of appalto indicators or other make indicators



Applications

- · Weight indicators
- Process indicators

Features of AND Wi-fi

- Facility to set channel ID using command
- Facility to set Wi-Fi transmission power using command
- Facility to configure the wireless display



Beneifits

- Distance of operation up to 150 meter
- Reduces installation cost & time
- No need of cable, casing capping, laying, digging etc.
- Avoids breakdown due to chances of cable cut because of rodents, heavy load
- Many wireless displays can run with one weight indicator / transmitter
- Field settable channel ID to run more than one set in same premises without any interference
- Wireless displays used with appalto Indicator
 having inbuilt Wi-Fi provides control for setting
 channel ID, transmission power and configuration

Features of Wi-fi Transmitter

- Wi-Fi transmitter is available in two versions
 - For connecting to TTD port
 - For connecting to RS232 port
- Field settable channel ID (max 4) using DIP switches

Marketed by:

Kanta King Technologies Pvt. Ltd. C-25, 2nd Floor, DSIDC Complex, Kirti Nagar, New Delhi - 110015, INDIA



+91.9560915555



info@kantaking.com



www.kantaking.com



Specifications for 2.3" 5 Digit

Model	2.3" 5 digit	
Display Digit Height	50 mm	
Dimensions Window	245 x 70	
Slot (W) x (H) in mm		
Outer Dimensions complete	470 x 114 x 55	
display unit (W) x (H) x (D) in mm		
Weight (approx.)	2.1 Kg	



Model	2.3" 6 digit	
Display Digit Height	50 mm	
Dimensions Window	310 x 72	
Slot (W) x (H) in mm		
Outer Dimensions complete	470 x 114 x 55	
display unit (W) x (H) x (D) in mm		
Weight (approx.)	2.1 Kg	



Model	4" 6 digit	
Display Digit Height	100 mm	
Dimensions Window	544 x 126	
Slot (W) x (H) in mm		
Outer Dimensions complete	760 x 180 x 50	
display unit (W) x (H) x (D) in mm		
Weight (approx.)	4.9 Kg	



Channel no.	Switch 1	Switch 2	Switch 3	Switch 4
1	OFF	OFF	OFF	OFF
2	OFF	ON	OFF	OFF
3	ON	OFF	OFF	OFF
4	ON	ON	OFF	OFF









Marketed by:

Kanta King Technologies Pvt. Ltd. C-25, 2nd Floor, DSIDC Complex, Kirti Nagar, New Delhi - 110015, INDIA



+91.9560915555



info@kantaking.com



www.kantaking.com

